

V. Conclusion

The sensor design consists of a two dimensional square lattice photonic crystal structure with a line defect. It is simulated and analysed for detecting different liquids in air and water. Visibly distinct shift in both wavelength and frequency are observed, proving the sensor to be sensitive to even a smallest change in the input liquid. Photonic crystal structure with line defect provides better sensitivity as compared to other photonic crystal design or other optical fiber sensor design. The sensor has sensitivity of the order of 0.000288 /RIU and the spectrum shows distinct shifts in both frequency and wavelength. The design meets the fabrication requirements as the quality factor obtained is 134837.

References

[1]. Optical properties of photonic crystals – K Sakoda.

[2]. Mekis A, Chen J C, Kurland I, Fan S, Villeneuve P R and Joannopoulos J D, “High transmission through sharp bends in photonic crystal waveguides,” *Phys. Rev. Lett.* 77, 3780-3790(1996).

[3]. Baba T, Fukaya N, and Yokokura J, “Observation of light propagation in photonic crystal optical waveguides with bends”, *Electron. Lett.* 35, 654- 655(1999).

[4]. Chutinan A, and Noda S, “Highly confined waveguides and waveguide bends in three-dimensional photonic crystal”, *Appl. Phys. Lett.* 75, 3739-3741(2000).

[5]. Tokushima M, Kosaka H, Tomita A and Yamada H, “Lightwave propagation through a 120° sharply bent single-line-defect photonic crystal waveguide” *Appl. Phys. Lett.* 76, 952-954(2000).

[6]. Lee M, and Fauchet P M, “Two-dimensional silicon photonic crystal based biosensing platform for protein

detection”, *Optics Express* 15, 4530- 4535(2007).

[7]. Photonic crystals modeling the flow of light by John D. Joannopoulos, Steven G. Johnson, Robert D. Meade.

[8]. Guided modes in photonic crystal slabs- Steven G. Johnson, Shanhui Fan, Pierre R. Villeneuve, and J. D. Joannopoulos, Department of Physics, Massachusetts Institute of Technology, Cambridge, Massachusetts 02139 -- *PHYSICAL REVIEW B – AUGUST 1999*.

[9]. Structural Tuning of Guiding Modes of Line-Defect Waveguides of Silicon-on-Insulator Photonic Crystal Slabs - Masaya Notomi, A Shinya, K Yamada, J Takahashi, C Takahashi, and I Yokohama- *IEEE JOURNAL OF QUANTUM ELECTRONICS*, VOL. 38, NO. 7, JULY 2002.

[10]. Existence of a photonic band gap in two dimensions-- R. D. Meade, A. M. Rappe, K. D. Brommer and J. D. Joannopoulos - *Appl. Phys. Lett.* 61, 495 (1992).

[11]. “Fabricated MEMS” by H. H. H. and Nagel, Naval Research Labs, NRL/MR-99-6336- 7975 (downloadable)

[12]. “Fiber Optic Sensors for Detection of Toxic and Biological Threats” Mahmoud El-Sherif *, alitkumar Bansal and Jianming Yuan ISSN 1424-8220 © 2007 by MDPI www.mdpi.org/sensors.

[13]. “Fibre Optic Sensors for Selected Wastewater Characteristics” Su Sin Chong 1, A. R. Abdul Aziz 1,* and Sulaiman W. Harun 2 .ISSN 1424-8220. www.mdpi.com/journal/sensors .

[14]. “Tunable ultracompact electro-optical photonic crystal ring resonator” Cheng-Yang Liu* Journal of Modern Optics, 2013 Vol. 60, No. 16, 1337–1342, <http://dx.doi.org/10.1080/09500340.2013.837979>.

[15]. “Photonic Crystals: From Theory to Practice” by Steven G. Johnson.